NSN 5985-01-273-9820



| Fixed Attenuator - Page 1 of 2 | Gr |
|---|----|
| View Online at https://aerobasegroup.com/nsn/5985-01-273-9820 | |
| Application Design: | |
| Transmission line | |
| Body Material: | |
| Brass | |
| Body Style: | |
| Rectangular terminal/terminals on opposite surfaces | |
| Body Surface Treatment: | |
| Gold plated, mil-g-45204 | |
| Overall Length: | |
| Between 0.748 inches and 0.755 inches | |
| Overall Height: | |
| Between 0.121 inches and 0.140 inches | |
| Overall Width: | |
| Between 0.248 inches and 0.255 inches | |
| Operating Tempurature Range: | |
| -0.0/+65.0 degrees celsius | |
| Voltage Standing Wave Ratio: | |
| 1.20 | |
| Input Impedance Rating In Ohms: | |
| 50.0 | |
| Output Impedance Rating In Ohms: | |
| 50.0 | |
| Power Rating: | |
| 1.0 watts average and 100.0 watts peak | |
| Rf Signal Attenuation In Decibels: | |
| 3.0 | |
| Attenuation Accuracy In Decibels: | |
| -0.20/+0.20 | |
| Mounting Method: | |
| Printed circuit | |
| Terminal Type And Quantity: | |
| 2 ribbon | |
| Cognizant Service: | |
| Usn | |
| Precious Material And Location: | |
| External surfaces gold | |

External surfaces gold

Precious Material:

Gold

Specification Data:

10001-3256559 manufacturers source control

Shelf Life:

N/a

NSN 5985-01-273-9820

Fixed Attenuator - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A20000