NSN 5985-01-273-9822

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-273-9822

Application Design:

Transmission line

Body Style:

Cylindrical w/side terminals

Overall Length:

2.595 inches

Bolt Circle Diameter:

1.234 inches

Overall Width:

2.250 inches

Body Diameter:

1.630 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.125 inches

Body Length:

Body Length.

1.840 inches

Unthreaded Mounting Hole Diameter:

0.136 inches

Voltage Standing Wave Ratio:

1.40

Coaxial Connector Series Designation:

Sma

Power Rating:

1.0 watts average

Insertion Loss At Minimum Attenuation In Maximum Decibels:

1.0

Overall Attenuation Range In Decibels:

+0.0/+15.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

3 unthreaded hole

Frequency Range:

Between 320.000 megahertz and 800.000 megahertz

Adjustment Device Type And Quantity:

1 shaft

Mounting Facility Pattern:

Three position circular

Shaft Type:

Round, slotted

NSN 5985-01-273-9822

Variable Attenuator - Page 2 of 2



Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0