## NSN 5985-01-273-9822

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-273-9822

Application Design:
Transmission line
Body Style:
Cylindrical w/side terminals
Overall Length:
2.595 inches
Bolt Circle Diameter:
1.234 inches
Overall Width:
2.250 inches
Body Diameter:
1.630 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.125 inches
Body Length:
1.840 inches
Unthreaded Mounting Hole Diameter:
0.136 inches
Voltage Standing Wave Ratio:
1.40
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
1.0
Overall Attenuation Range In Decibels:
+0.0/+15.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
3 unthreaded hole
Frequency Range:
Between 320.000 megahertz and 800.000 megahertz
Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:
Three position circular
Shaft Type:

Round, slotted

## NSN 5985-01-273-9822

Variable Attenuator - Page 2 of 2



Impedance Rating In Ohms	lmp	edance	Rating	In	<b>Ohms</b>
--------------------------	-----	--------	--------	----	-------------

50.0 input-output

**Terminal Type And Quantity:** 

2 connector, coaxial, female

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0