

View Online at <https://aerobasegroup.com/nsn/5985-01-274-1036>

**Application Design:**

Printed circuit board

**Body Style:**

Rectangular, terminals on one surface

**Overall Length:**

1.350 inches

**Overall Height:**

0.750 inches

**Overall Width:**

Between 0.760 inches and 0.800 inches

**Shaft Diameter:**

Between 0.120 inches and 0.130 inches

**Bushing Length:**

0.500 inches

**Shaft Length:**

0.600 inches

**Voltage Standing Wave Ratio:**

1.30 and 1.50

**Power Rating:**

0.5 watts average

**Insertion Loss At Minimum Attenuation In Maximum Decibels:**

1.0

**Overall Attenuation Range In Decibels:**

+0.0/+20.0

**Attenuation Variation Method:**

Continuous

**Frequency Range:**

Between 0.000 hertz and 200.000 megahertz

**Overall Attenuation Accuracy In Decibels:**

-0.25/+0.25

**Adjustment Device Type And Quantity:**

1 shaft

**Shaft Type:**

Round, slotted

**Impedance Rating In Ohms:**

50.0 input-output

**Terminal Type And Quantity:**

4 pin

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A223a0