NSN 5985-01-274-3991

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-274-3991

Application Design:
Printed circuit board
Body Material:
Brass
Body Style:
Irregular
Overall Length:
5.500 inches
Overall Height:
1.000 inches
Overall Width:
1.250 inches
Voltage Standing Wave Ratio:
1.00 and 1.02 and 1.30 and 1.40
Insertion Loss At Minimum Attenuation In Maximum Decibels:
4.5
Overall Attenuation Range In Decibels:
+0.0/+15.5
Attenuation Variation Method:
Stepped
Mounting Facility Type And Quantity:
38 terminal
Frequency Range:
Between 55.000 megahertz and 65.000 megahertz
Segment Attenuation Accuracy In Decibels:
-0.25/+0.25
Adjustment Device Type And Quantity:
1 electronic, voltage controlled
Impedance Rating In Ohms:
50.0 input and 50.0 output
Special Features:
External surfaces to be tin plated; all surfaces except bottom and pins to be finished with semi-gloss enamel; bottom and pins to be gold
plated
Precious Material And Location:
External surfaces gold
Precious Material:
Gold
Terminal Type And Quantity:
38 pin
Fsc Application Data:
Antennas, waveguides, and related equipment

N/a

Shelf Life:

NSN 5985-01-274-3991

Variable Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0