## NSN 5985-01-274-3992

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-274-3992 **Application Design:** Printed circuit board **Body Style:** Irregular **Overall Length:** 6.500 inches **Overall Height:** 0.750 inches **Overall Width:** 1.250 inches **Voltage Standing Wave Ratio:** 1.00 and 1.30 and 1.40 **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 5.5 **Overall Attenuation Range In Decibels:** +0.0/+31.5 **Attenuation Variation Method:** Stepped **Mounting Facility Type And Quantity:** 38 terminal Frequency Range: Between 55.000 megahertz and 65.000 megahertz **Overall Attenuation Accuracy In Decibels:** -0.25/+0.25 **Adjustment Device Type And Quantity:** 1 electronic, voltage controlled Impedance Rating In Ohms: 50.0 input-output **Precious Material And Location:** Contact surfaces gold **Precious Material:** Gold **Terminal Type And Quantity:** 38 pin **Fsc Application Data:** Antennas, waveguides, and related equipment Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

## NSN 5985-01-274-3992

Variable Attenuator - Page 2 of 2



Fiig:

A223a0