

View Online at <https://aerobasegroup.com/nsn/5985-01-274-3994>

Application Design:

Printed circuit board

Body Style:

Rectangular, terminals on one surface

Overall Length:

1.350 inches

Overall Height:

0.750 inches

Overall Width:

0.800 inches

Shaft Diameter:

Between 0.120 inches and 0.130 inches

Bushing Length:

0.500 inches

Shaft Length:

0.600 inches

Voltage Standing Wave Ratio:

1.50

Power Rating:

0.5 watts average

Insertion Loss At Minimum Attenuation In Maximum Decibels:

2.0

Overall Attenuation Range In Decibels:

+0.0/+15.5

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

1 printed circuit

Frequency Range:

Between 400.000 megahertz and 600.000 megahertz

Overall Attenuation Accuracy In Decibels:

-0.20/+0.20

Adjustment Device Type And Quantity:

1 shaft

Shaft Type:

Round, slotted

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

4 pin

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0