NSN 5985-01-274-7909

Rectangular terminal/terminals on three surfaces

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:
Any acceptable
Body Style:

Body Surface Treatment:



View Online at https://aerobasegroup.com/nsn/5985-01-274-7909

Any acceptable
Overall Length:
0.147 inches
Overall Height:
0.035 inches
Overall Width:
0.124 inches
Operating Tempurature Range:
-55.0/+150.0 degrees celsius
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Power Rating:
0.5 watts average
Rf Signal Attenuation In Decibels:
16.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz
Attenuation Accuracy Reference Frequency:
4.0 gigahertz
Attenuation Accuracy In Decibels:
-0.40/+0.40
Unpackaged Unit Weight:
0.003 pounds
Mounting Method:
Terminal
Terminal Type And Quantity:
3 surface contact
Frequency Range:
Between 0.000 hertz and 4.000 gigahertz
Precious Material And Location:
Contact surfaces gold and contact surfaces platinum

NSN 5985-01-274-7909

Fixed Attenuator - Page 2 of 2



Precious Material:
Gold and platinum
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A20000