

View Online at <https://aerobasegroup.com/nsn/5985-01-274-7910>

Application Design:

Transmission line

Body Material:

Steel, qq-s-763, class 302 and steel, qq-s-763, class 304

Body Style:

Err-090

Body Surface Treatment:

Passivated

Overall Length:

0.860 inches

Overall Diameter:

0.310 inches

Operating Temperature Range:

-54.0/+125.0 degrees celsius

Voltage Standing Wave Ratio:

1.15 and 1.25 and 1.35

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Sma

Power Rating:

2.0 watts average and 100.0 watts peak

Rf Signal Attenuation In Decibels:

1.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz

Attenuation Accuracy Reference Frequency:

12.4 gigahertz

Attenuation Accuracy In Decibels:

-0.30/+0.30

Connection Type Per Function:

Female input and male output

Unpackaged Unit Weight:

0.140 ounces

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

Precious Material And Location:

Contacts gold

Precious Material:

Gold

Specification Data:

26916-037-003295 manufacturers specification control

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A20000