NSN 5985-01-275-5449

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-275-5449 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Err-090 **Terminal Material:** Steel, stainless **Body Surface Treatment:** Any acceptable **Overall Length:** 1.240 inches **Overall Diameter:** 0.625 inches **Voltage Standing Wave Ratio:** 1.25 and 1.40 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 5.5 watts average and 0.2 kilowatts peak **Rf Signal Attenuation In Decibels:** 10.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+4.0 gigahertz and +4.0/+6.0 gigahertz **Attenuation Accuracy Reference Frequency:** 6.0 gigahertz **Attenuation Accuracy In Decibels:** -0.30/+0.30 **Connection Type Per Function:** Male input and female output **Unpackaged Unit Weight:** 0.500 ounces **Mounting Method:** Connector **Terminal Type And Quantity:**

2 connector

Frequency Range:

Between 0.000 hertz and 6.000 gigahertz

NSN 5985-01-275-5449

Fixed Attenuator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000