

View Online at <https://aerobasegroup.com/nsn/5985-01-277-0780>

Application Design:

Printed circuit board

Body Style:

Irregular

Overall Length:

Between 0.770 inches and 0.800 inches

Overall Height:

Between 0.385 inches and 0.400 inches

Overall Width:

Between 0.370 inches and 0.400 inches

Power Rating:

1.0 watts peak

Insertion Loss At Minimum Attenuation In Maximum Decibels:

4.7

Overall Attenuation Range In Decibels:

+0.0/+65.0

Attenuation Accuracy Reference Frequency:

12.0 megahertz

Attenuation Variation Method:

Stepped

Step Position Quantity:

5

Frequency Range:

Between 5.000 megahertz and 450.000 megahertz

Segment Attenuation Range In Decibels:

+0.00/+35.00 and +35.00/+40.00 and +40.00/+50.00 and +50.00/+60.00 and +60.00/+65.00

Adjustment Device Type And Quantity:

1 electronic, current controlled

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

8 pin

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A223a0