## NSN 5985-01-277-4927



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-277-4927 **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** Err-090 **Body Surface Treatment:** Any acceptable **Overall Length:** 1.490 inches **Overall Diameter:** 0.360 inches **Operating Tempurature Range:** -65.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.15 and 1.25 and 1.35 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 2.0 watts average **Rf Signal Attenuation In Decibels:** 50.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz **Attenuation Accuracy Reference Frequency:** 18.0 gigahertz **Attenuation Accuracy In Decibels:** -1.50/+1.50 **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz

**Fsc Application Data:** Antennas, waveguides, and related equipment Shelf Life: N/a

## NSN 5985-01-277-4927

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A20000