

View Online at <https://aerobasegroup.com/nsn/5985-01-277-5262>

Body Style:

Rectangular

Overall Length:

2.630 inches

Overall Height:

2.060 inches

Overall Width:

0.560 inches

Frequency Rating:

8.0 gigahertz 3rd frequency voltage standing wave ratio and 12.4 gigahertz 3rd frequency voltage standing wave ratio

Unthreaded Mounting Hole Diameter:

0.116 inches

Switch Type:

Nontransfer

Operating Temperature Range:

-35.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.40 3rd

Insertion Loss In Decibels:

0.40 3rd

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Minimum Crosstalk Rating In Decibels:

60.0 single

Actuator Operating Method:

Solid state

Actuator Current Type And Rating In Amps:

0.28 dc

Actuator Voltage In Volts:

Between 24.0 and 30.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

15.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

5

Mounting Facility Type And Quantity:

2 unthreaded hole

Material:

Copper alloy contact (s)

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Surface Treatment:

Nickel body outside surfaces

Terminal Type And Quantity:

3 receptacle, coaxial and 6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A158a0