

View Online at <https://aerobasegroup.com/nsn/5985-01-277-6061>

**Application Design:**

Transmission line

**Body Style:**

Coaxial type

**Overall Length:**

2.500 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.844 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.094 inches

**Overall Height:**

0.500 inches

**Overall Width:**

2.000 inches

**Voltage Standing Wave Ratio:**

1.70

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

5.0 watts average and 3.0 kilowatts peak

**Mounting Facility Screw Thread Series Designator:**

Unc

**Insertion Loss At Minimum Attenuation In Maximum Decibels:**

0.5

**Overall Attenuation Range In Decibels:**

+0.0/+15.0

**Attenuation Variation Method:**

Continuous

**Mounting Facility Type And Quantity:**

4 threaded hole

**Frequency Range:**

Between 1.500 gigahertz and 2.000 gigahertz

**Mounting Thread Quantity:**

40 per inch

**Adjustment Device Type And Quantity:**

1 slotted screw

**Mounting Facility Pattern:**

Four position rectangular

**Mounting Facility Screw Thread Diameter:**

0.112 inches

**Impedance Rating In Ohms:**

50.0 input-output

**Terminal Type And Quantity:**

2 connector, coaxial, female

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A223a0