NSN 5985-01-277-6061

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-277-6061

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.844 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.094 inches
Overall Height:
0.500 inches
Overall Width:
2.000 inches
Voltage Standing Wave Ratio:
1.70
Coaxial Connector Series Designation:
Sma
Power Rating:
5.0 watts average and 3.0 kilowatts peak
Mounting Facility Screw Thread Series Designator:
Unc
Unc Insertion Loss At Minimum Attenuation In Maximum Decibels:
Insertion Loss At Minimum Attenuation In Maximum Decibels:
Insertion Loss At Minimum Attenuation In Maximum Decibels: 0.5
Insertion Loss At Minimum Attenuation In Maximum Decibels: 0.5 Overall Attenuation Range In Decibels:
Insertion Loss At Minimum Attenuation In Maximum Decibels: 0.5 Overall Attenuation Range In Decibels: +0.0/+15.0
Insertion Loss At Minimum Attenuation In Maximum Decibels: 0.5 Overall Attenuation Range In Decibels: +0.0/+15.0 Attenuation Variation Method:
Insertion Loss At Minimum Attenuation In Maximum Decibels: 0.5 Overall Attenuation Range In Decibels: +0.0/+15.0 Attenuation Variation Method: Continuous
Insertion Loss At Minimum Attenuation In Maximum Decibels: 0.5 Overall Attenuation Range In Decibels: +0.0/+15.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity:
Insertion Loss At Minimum Attenuation In Maximum Decibels: 0.5 Overall Attenuation Range In Decibels: +0.0/+15.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole
Insertion Loss At Minimum Attenuation In Maximum Decibels: 0.5 Overall Attenuation Range In Decibels: +0.0/+15.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range:
Insertion Loss At Minimum Attenuation In Maximum Decibels: 0.5 Overall Attenuation Range In Decibels: +0.0/+15.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 1.500 gigahertz and 2.000 gigahertz
Insertion Loss At Minimum Attenuation In Maximum Decibels: 0.5 Overall Attenuation Range In Decibels: +0.0/+15.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 1.500 gigahertz and 2.000 gigahertz Mounting Thread Quantity:
Insertion Loss At Minimum Attenuation In Maximum Decibels: 0.5 Overall Attenuation Range In Decibels: +0.0/+15.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 1.500 gigahertz and 2.000 gigahertz Mounting Thread Quantity: 40 per inch
Insertion Loss At Minimum Attenuation In Maximum Decibels: 0.5 Overall Attenuation Range In Decibels: +0.0/+15.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 1.500 gigahertz and 2.000 gigahertz Mounting Thread Quantity: 40 per inch Adjustment Device Type And Quantity:
Insertion Loss At Minimum Attenuation In Maximum Decibels: 0.5 Overall Attenuation Range In Decibels: +0.0/+15.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 1.500 gigahertz and 2.000 gigahertz Mounting Thread Quantity: 40 per inch Adjustment Device Type And Quantity: 1 slotted screw
Insertion Loss At Minimum Attenuation In Maximum Decibels: 0.5 Overall Attenuation Range In Decibels: +0.0/+15.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 1.500 gigahertz and 2.000 gigahertz Mounting Thread Quantity: 40 per inch Adjustment Device Type And Quantity: 1 slotted screw Mounting Facility Pattern:
Insertion Loss At Minimum Attenuation In Maximum Decibels: 0.5 Overall Attenuation Range In Decibels: +0.0/+15.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 1.500 gigahertz and 2.000 gigahertz Mounting Thread Quantity: 40 per inch Adjustment Device Type And Quantity: 1 slotted screw Mounting Facility Pattern: Four position rectangular

50.0 input-output

NSN 5985-01-277-6061

Variable Attenuator - Page 2 of 2



Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0