## NSN 5985-01-278-7206

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-278-7206 **Application Design:** Transmission line **Body Material: Brass Body Style:** Err-090 **Body Surface Treatment:** Passivated **Overall Length:** Between 0.840 inches and 0.880 inches **Overall Diameter:** 0.348 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.20 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 2.0 watts average and 200.0 watts peak **Rf Signal Attenuation In Decibels:** 10.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+4.0 gigahertz **Connection Type Per Function:** Female input and male output **Unpackaged Unit Weight:** 5.500 grams **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Shelf Life: N/a **Unit Of Measure:** 

## NSN 5985-01-278-7206

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000