NSN 5985-01-280-3043

Variable Attenuator - Page 1 of 2

Yes - demil/mli



View Online at https://aerobasegroup.com/nsn/5985-01-280-3043

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.570 inches
Overall Height:
2.560 inches
Overall Width:
4.000 inches
Voltage Standing Wave Ratio:
1.50 and 1.60 and 1.70
Coaxial Connector Series Designation:
N
Power Rating:
1.3 watts average and 200.0 watts peak
Insertion Loss At Minimum Attenuation In Maximum Decibels:
1.2
Overall Attenuation Range In Decibels:
+0.0/+11.0
Attenuation Accuracy Reference Frequency:
18.0 gigahertz
Attenuation Variation Method:
Stepped
Step Position Quantity:
11
Attenuation Per Step In Decibels:
1.0
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Segment Attenuation Range In Decibels:
+0.00/+1.00 and +1.00/+2.00 and +2.00/+3.00 and +3.00/+4.00 and +4.00/+5.00 and +5.00/+6.00 and +6.00/+7.00 and +7.00/+8.00 and
+8.00/+9.00 and +9.00/+10.00 and +10.00/+11.00
Adjustment Device Type And Quantity:
2 knob
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

NSN 5985-01-280-3043

Variable Attenuator - Page 2 of 2



Fiig:

A223a0