NSN 5985-01-283-1283

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:



View Online at https://aerobasegroup.com/nsn/5985-01-283-1283

Plastic, epoxy resin
Body Style:
Rectangular terminal/terminals on three surfaces
Terminal Material:
Any acceptable
Terminal Surface Treatment:
Gold plated and platinum
Body Surface Treatment:
Passivated
Overall Length:
Between 0.137 inches and 0.157 inches
Overall Height:
0.030 inches
Overall Width:
Between 0.112 inches and 0.132 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Power Rating:
0.5 watts average
Rf Signal Attenuation In Decibels:
6.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+12.0 gigahertz
Attenuation Accuracy Reference Frequency:
18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Mounting Method:
Mounting Method: Terminal
_
Terminal
Terminal Terminal Type And Quantity:
Terminal Terminal Type And Quantity: 3 surface contact

NSN 5985-01-283-1283

Fixed Attenuator - Page 2 of 2



Precious Material:
Gold and platinum
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A20000