NSN 5985-01-283-1285

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-283-1285

Application Design: Transmission line Body Material:

Plastic, epoxy resin

Body Style:

Rectangular terminal/terminals on three surfaces

Body Surface Treatment:

Passivated

Overall Length:

0.145 inches

Overall Height:

0.122 inches

Overall Width:

Between 0.112 inches and 0.132 inches

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Voltage Standing Wave Ratio:

1.30

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Power Rating:

0.5 watts average

Rf Signal Attenuation In Decibels:

5.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+12.0 gigahertz

Attenuation Accuracy In Decibels:

-0.50/+0.50

Unpackaged Unit Weight:

0.003 pounds

Mounting Method:

Terminal

Terminal Type And Quantity:

3 surface contact

Frequency Range:

Between 0.000 hertz and 12.000 gigahertz

Precious Material And Location:

Terminals gold and terminals platinum

Precious Material:

Gold and platinum

NSN 5985-01-283-1285

Fixed Attenuator - Page 2 of 2



Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A20000