NSN 5985-01-283-2479

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-283-2479

Cross Sectional Shape:

Internal, rectangular double ridged external, rectangular

Thread Class:

2b all flanges first connection facility

Thread Direction:

Right-hand all flanges first connection facility

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.087 inches all flanges and 1.093 inches all flanges

Flange Inside Height:

0.503 mils all flanges and 0.509 centimeters all flanges

Flange Outside Width:

1.954 inches all flanges and 1.984 inches all flanges

Flange Outside Height:

1.376 inches all flanges and 1.406 inches all flanges

Flange Depth:

0.245 inches all flanges

Flange Connecting Hole Diameter:

0.145 inches all flanges second connection facility and 0.148 inches all flanges second connection facility

Voltage Standing Wave Ratio:

1.20

Waveguide Outside Width:

1.340 inches

Thread Size:

0.138 inches all flanges first connection facility

Waveguide Inside Width:

Between 1.210 inches and 1.218 inches

Waveguide Inside Height:

Between 0.626 inches and 0.634 inches

Waveguide Outside Height:

0.750 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges second connection facility

Flange Style:

Contact, double ridge type all flanges

Waveguide Length:

2.750 inches

Flexibility:

Rigid single tubing segment

NSN 5985-01-283-2479 Waveguide Assembly - Page 2 of 2



Material:
Aluminum alloy single tubing segment and flange
Style Designator:
Straight type
Thread Series Designator:
Unc all flanges first connection facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A073a0