## NSN 5985-01-283-3068

Fixed Attenuator - Page 1 of 2



- mour mondator in ago in or i
View Online at https://aerobasegroup.com/nsn/5985-01-283-3068
Application Design:
Transmission line
Body Material:
Brass
Body Style:
Err-090
Overall Length:
1.125 inches
Overall Diameter:
0.313 inches
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
End Application:
Submarine surveillance systems. Type 18 periscope.
Voltage Standing Wave Ratio:
1.15 and 1.40
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Wpm
Power Rating:
2.0 watts average
Rf Signal Attenuation In Decibels:
10.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+18.0 gigahertz and +18.0/+40.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Connection Type Per Function:
Female input and male output
Mounting Method:
Connector
Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 40.000 gigahertz

**Criticality Code Justification:** 

Feat

**Special Features:** 

Weapon system essential

## NSN 5985-01-283-3068

Fixed Attenuator - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000