NSN 5985-01-283-4452

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-283-4452

Transmission line Body Material: Any acceptable Body Style: Err-090 Body Surface Treatment: Any acceptable Overall Length: 2.750 inches Overall Diameter: 0.812 inches Voltage Standing Wave Ratio: 1.15 and 1.25 and 1.35 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Any acceptable Body Style: Err-090 Body Surface Treatment: Any acceptable Overall Length: 2.750 inches Overall Diameter: 0.812 inches Voltage Standing Wave Ratio: 1.15 and 1.25 and 1.35 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Body Style: Err-090 Body Surface Treatment: Any acceptable Overall Length: 2.750 inches Overall Diameter: 0.812 inches Voltage Standing Wave Ratio: 1.15 and 1.25 and 1.35 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Err-090 Body Surface Treatment: Any acceptable Overall Length: 2.750 inches Overall Diameter: 0.812 inches Voltage Standing Wave Ratio: 1.15 and 1.25 and 1.35 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Body Surface Treatment: Any acceptable Overall Length: 2.750 inches Overall Diameter: 0.812 inches Voltage Standing Wave Ratio: 1.15 and 1.25 and 1.35 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Any acceptable Overall Length: 2.750 inches Overall Diameter: 0.812 inches Voltage Standing Wave Ratio: 1.15 and 1.25 and 1.35 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Overall Length: 2.750 inches Overall Diameter: 0.812 inches Voltage Standing Wave Ratio: 1.15 and 1.25 and 1.35 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
2.750 inches Overall Diameter: 0.812 inches Voltage Standing Wave Ratio: 1.15 and 1.25 and 1.35 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Overall Diameter: 0.812 inches Voltage Standing Wave Ratio: 1.15 and 1.25 and 1.35 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Voltage Standing Wave Ratio: 1.15 and 1.25 and 1.35 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Voltage Standing Wave Ratio: 1.15 and 1.25 and 1.35 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
1.15 and 1.25 and 1.35 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Coaxial Connector Series Designation: N Power Rating: 2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Coaxial Connector Series Designation: N Power Rating: 2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Power Rating: 2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Power Rating: 2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
2.0 watts average and 100.0 watts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
+0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
18.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
-0.60/+0.60 Connection Type Per Function: Female input and male output
Connection Type Per Function: Female input and male output
Female input and male output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:

N/a

NSN 5985-01-283-4452

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A20000