

View Online at <https://aerobasegroup.com/nsn/5985-01-283-5932>

Cross Sectional Shape:

Internal, rectangular double ridged external, rectangular

Thread Class:

2b all flanges first connection facility

Thread Direction:

Right-hand all flanges first connection facility

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.405 inches all flanges and 0.411 inches all flanges

Flange Inside Height:

0.251 inches all flanges and 0.257 inches all flanges

Flange Outside Width:

0.860 inches all flanges and 0.890 inches all flanges

Flange Outside Height:

0.860 inches all flanges and 0.890 inches all flanges

Flange Depth:

0.188 inches all flanges

Flange Connecting Hole Diameter:

0.116 inches all flanges third connection facility and 0.118 inches all flanges third connection facility

Voltage Standing Wave Ratio:

1.20

Waveguide Outside Width:

0.540 inches

Thread Size:

0.112 inches all flanges first connection facility

Waveguide Inside Width:

Between 0.286 inches and 0.290 inches

Waveguide Inside Height:

Between 0.132 inches and 0.136 inches

Waveguide Outside Height:

0.400 inches

Flange Connecting Facility And Quantity:

2 unthreaded hole all flanges second connection facility

Flange Style:

Contact, double ridge type all flanges

Waveguide Length:

5.200 inches

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy single tubing segment and flange

Style Designator:

Straight type

Thread Series Designator:

Unc all flanges first connection facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiiig:

A073a0