## NSN 5985-01-283-6706

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-283-6706 **Application Design:** Transmission line **Body Style:** Coaxial type **Overall Length:** Between 3.000 inches and 3.020 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.950 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.150 inches **Overall Height:** Between 1.140 inches and 1.160 inches **Overall Width:** Between 0.950 inches and 0.970 inches **Coaxial Connector Series Designation:** Sma **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 3.8 **Overall Attenuation Range In Decibels:** +0.0/+18.0 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 4 flange w/mounting hole Frequency Range: Between 0.200 megahertz and 0.400 megahertz **Overall Attenuation Accuracy In Decibels:** -1.00/+1.00 **Adjustment Device Type And Quantity:** 1 slotted screw **Mounting Facility Pattern:** Four position rectangular Impedance Rating In Ohms: 50.0 input-output **Terminal Type And Quantity:** 2 connector, coaxial, male Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

## NSN 5985-01-283-6706

Variable Attenuator - Page 2 of 2



Fiig:

A223a0