NSN 5985-01-286-1580

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/psn/5085-01-286-1580

view Online at https://aerobasegroup.com/nsn/5985-01-286-1560
Application Design:
Transmission line
Body Material:
Steel
Body Style:
Rectangular, terminal/terminals on opposite surfaces
Overall Length:
2.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.600 inches
Overall Height:
1.620 inches
Overall Width:
0.800 inches
Mounting Hole/stud Quantity:
4
Body Length:
1.880 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.500 inches
Operating Tempurature Range:
-0.0/+70.0 degrees celsius
Voltage Standing Wave Ratio:
1.40
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
0.5 watts average
Rf Signal Attenuation In Decibels:
32.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+1.5 gigahertz
Mounting Facility Thread Size And Series/type Designator:
2-56 unc
Attenuation Accuracy Reference Frequency:
1.0 gigahertz

-0.30/+0.50

Attenuation Accuracy In Decibels:

NSN 5985-01-286-1580

Fixed Attenuator - Page 2 of 2



Connection Type Per Function:
Female input and male output
Mounting Method:
Threaded hole
Terminal Type And Quantity:
3 connector
Frequency Range:
Between 0.000 hertz and 1.500 gigahertz
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A20000