## NSN 5985-01-288-6737

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:

Brass



View Online at https://aerobasegroup.com/nsn/5985-01-288-6737

Body Style:
Err-090
Body Surface Treatment:
Anodized
Overall Length:
Between 2.200 inches and 2.320 inches
Overall Diameter:
1.000 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
<b>Coaxial Connector Series Designation:</b>
Sma
Power Rating:
10.0 watts average and 3.0 kilowatts peak
Rf Signal Attenuation In Decibels:
30.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz
Attenuation Accuracy Reference Frequency:
4.0 gigahertz
Attenuation Accuracy In Decibels:
-0.80/+1.30
Connection Type Per Function:
Female input and male output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 4.000 gigahertz
Shelf Life:
N/a

## NSN 5985-01-288-6737

Fixed Attenuator - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000