## NSN 5985-01-291-5548



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-291-5548 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Err-090 **Body Surface Treatment:** Any acceptable **Overall Length:** 3.050 inches **Overall Diameter:** 0.820 inches **Voltage Standing Wave Ratio:** 1.30 and 1.50 and 1.70 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation: Rf Signal Attenuation In Decibels:** 10.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+0.5 gigahertz and +0.5/+1.0 gigahertz and +1.0/+1.5 gigahertz **Attenuation Accuracy Reference Frequency:** 1.5 gigahertz **Attenuation Accuracy In Decibels:** -0.40/+0.40 **Connection Type Per Function:** Female input and male output **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 1.500 gigahertz **Fsc Application Data:** Antennas, waveguides, and related equipment

Shelf Life: N/a

**Unit Of Measure:** 

--

## NSN 5985-01-291-5548

Fixed Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A20000