NSN 5985-01-292-2384

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-292-2384

Application Design: Transmission line **Body Material:** Aluminum alloy **Body Style:** Rectangular, terminal/terminals on opposite surfaces **Overall Length:** 6.890 inches **Overall Height:** 3.060 inches **Overall Width:** 3.060 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.10 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Ν **Power Rating:** 150.0 watts average and 10.0 kilowatts peak **Rf Signal Attenuation In Decibels:** 20.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+1.5 gigahertz **Attenuation Accuracy In Decibels:** -0.50/+0.50 **Connection Type Per Function:** Female input and male output **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 1.500 gigahertz Shelf Life:

N/a

Unit Of Measure:

NSN 5985-01-292-2384

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000