

View Online at <https://aerobasegroup.com/nsn/5985-01-292-7938>

Body Style:

Rectangular

Overall Length:

2.690 inches

Overall Height:

1.750 inches

Overall Width:

1.750 inches

Frequency Rating:

8.0 gigahertz 3rd frequency voltage standing wave ratio and 12.4 gigahertz 3rd frequency voltage standing wave ratio

Unthreaded Mounting Hole Diameter:

0.144 inches

Switch Type:

Nontransfer

Operating Temperature Range:

-35.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.50 4th

Insertion Loss In Decibels:

1.50 4th

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Minimum Crosstalk Rating In Decibels:

60.0 single

Actuator Operating Method:

Solid state

Actuator Current Type And Rating In Amps:

0.16 dc

Actuator Voltage In Volts:

Between 24.0 and 30.0

Switch Operation Sequence:

Makes before breaks

Switching Time:

15.0 milliseconds

Pole Quantity:

1

Throw Quantity:

6

Coupling Position Quantity:

8

Mounting Facility Type And Quantity:

4 unthreaded hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Special Features:

W/9 contact male connector

Material:

Copper alloy contact (s)

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Surface Treatment:

Nickel body outside surfaces

Supplementary Features:

Used on f-15 acft

Terminal Type And Quantity:

1 connector, receptacle and 7 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0