

NSN 5985-01-293-2164 Variable Attenuator - Page 1 of 2	AeroBase Group
View Online at https://aerobasegroup.com/nsn/5985-01-293-2164	
Application Design:	
Transmission line	
Body Material:	
Aluminum	
Overall Length:	
Between 1.560 inches and 1.580 inches	
Center To Center Distance Between Mounting Facilities Parallel To Width:	
0.810 inches	
Overall Height:	
Between 0.490 inches and 0.510 inches	
Overall Width:	

Between 0.990 inches and 1.010 inches

Operating Tempurature Range:

-54.0/+95.0 degrees celsius

Voltage Standing Wave Ratio:

1.50

Coaxial Connector Series Designation:

Sma

Power Rating:

1.0 watts peak

Mounting Facility Screw Thread Series Designator:

Unc

2.5

Insertion Loss At Minimum Attenuation In Maximum Decibels:

Overall Attenuation Range In Decibels:

+0.0/+10.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

4 threaded hole

Mounting Thread Quantity:

56 per inch

Adjustment Device Type And Quantity:

1 electronic, voltage controlled

Mounting Facility Pattern:

Four position rectangular

Mounting Facility Screw Thread Diameter:

0.086 inches

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female and 3 solder stud

NSN 5985-01-293-2164

Variable Attenuator - Page 2 of 2



Fsc Application Data	Fsc	Ap	plic	atio	n D	ata
----------------------	-----	----	------	------	-----	-----

Antennas, waveguides, and related equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0