NSN 5985-01-293-7594

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-293-7594

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.2225 inches all flanges and 0.2255 inches all flanges

Flange Inside Height:

0.1105 inches all flanges and 0.1135 inches all flanges

Flange Outside Diameter:

1.123 inches all flanges and 1.125 inches all flanges

Flange Depth:

0.225 inches all flanges and 0.275 inches all flanges

Flange Connecting Hole Diameter:

0.116 inches single flange first connection facility and 0.123 inches single flange first connection facility

Voltage Standing Wave Ratio:

1.02

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Inside Width:

Between 0.2225 inches and 0.2255 inches

Waveguide Inside Height:

Between 0.1105 inches and 0.1135 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole single flange second connection facility

Flange Style:

Cover type all flanges

Waveguide Length:

14.970 inches

Waveguide Center To Center Distance:

2.260 inches

Flexibility:

Rigid single tubing segment

Material:

Nickel silver single tubing segment

Precious Material And Location:

Flange face silver

Precious Material:

Silver

Surface Treatment:

Silver all flange inside surfaces

NSN 5985-01-293-7594

Waveguide Assembly - Page 2 of 2

Style Designator:

Offset bend type

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A073a0

