NSN 5985-01-295-0654

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-295-0654

Application Design:
Transmission line
Overall Length:
4.690 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.000 inches
Overall Height:
1.440 inches
Overall Width:
1.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.000 inches
Voltage Standing Wave Ratio:
1.41
Coaxial Connector Series Designation:
Sma
Insertion Loss At Minimum Attenuation In Maximum Decibels:
4.0
Overall Attenuation Range In Decibels:
+0.0/+127.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
127
Attenuation Per Step In Decibels:
1.0
1.0 Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 4 threaded hole
Mounting Facility Type And Quantity: 4 threaded hole Frequency Range:
Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 900.000 megahertz and 1300.000 megahertz
Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 900.000 megahertz and 1300.000 megahertz Overall Attenuation Accuracy In Decibels:
Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 900.000 megahertz and 1300.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50
Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 900.000 megahertz and 1300.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Adjustment Device Type And Quantity:
Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 900.000 megahertz and 1300.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Adjustment Device Type And Quantity: 1 electronic, programmable
Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 900.000 megahertz and 1300.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Adjustment Device Type And Quantity: 1 electronic, programmable Mounting Facility Pattern:
Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 900.000 megahertz and 1300.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Adjustment Device Type And Quantity: 1 electronic, programmable Mounting Facility Pattern: Four position rectangular
Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 900.000 megahertz and 1300.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Adjustment Device Type And Quantity: 1 electronic, programmable Mounting Facility Pattern: Four position rectangular Impedance Rating In Ohms:
Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 900.000 megahertz and 1300.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Adjustment Device Type And Quantity: 1 electronic, programmable Mounting Facility Pattern: Four position rectangular Impedance Rating In Ohms: 50.0 input-output

N/a

NSN 5985-01-295-0654

Variable Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0