

View Online at <https://aerobasegroup.com/nsn/5985-01-295-2309>

**Application Design:**

Transmission line

**Body Style:**

Rectangular, terminals on one surface

**Overall Length:**

1.350 inches

**Overall Height:**

0.660 inches

**Overall Width:**

0.800 inches

**Bushing Length:**

0.570 inches

**Voltage Standing Wave Ratio:**

1.50 and 2.00

**Insertion Loss At Minimum Attenuation In Maximum Decibels:**

2.0

**Overall Attenuation Range In Decibels:**

+0.0/+15.5

**Attenuation Accuracy Reference Frequency:**

600.0 megahertz

**Attenuation Variation Method:**

Stepped

**Step Position Quantity:**

2

**Attenuation Per Step In Decibels:**

5.0

**Mounting Facility Type And Quantity:**

1 threaded stud

**Frequency Range:**

Between 400.000 megahertz and 600.000 megahertz

**Segment Attenuation Range In Decibels:**

+0.00/+15.50

**Adjustment Device Type And Quantity:**

1 shaft

**Shaft Type:**

Round, slotted

**Impedance Rating In Ohms:**

50.0 input-output

**Terminal Type And Quantity:**

4 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A223a0