NSN 5985-01-295-3380

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-295-3380

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

3b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

3.120 inches second flange and 3.128 inches second flange

Flange Inside Height:

1.335 inches second flange and 1.345 inches second flange

Flange Outside Width:

4.500 inches second flange

Flange Outside Height:

3.000 inches second flange

Flange Depth:

0.370 inches second flange and 0.380 inches second flange

Flange Connecting Hole Diameter:

0.262 inches second flange all connection facilities and 0.268 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.06

Waveguide Outside Width:

3.000 inches

Thread Size:

0.190 inches first flange all connection facilities

Waveguide Inside Width:

2.840 inches

Waveguide Inside Height:

1.340 inches

Waveguide Outside Height:

1.500 inches

Flange Connecting Facility And Quantity:

8 threaded hole first flange all connection facilities

Flange Style:

Contact type second flange

Waveguide Length:

6.165 inches

NSN 5985-01-295-3380

Waveguide Assembly - Page 2 of 2



Waveguide Center To Center Distance: 2.584 inches Flexibility: Rigid single tubing segment Material: Copper alloy single tubing segment and flange Style Designator: Offset bend type Thread Series Designator: Unf first flange all connection facilities Shelf Life: N/a Unit Of Measure: -- Demilitarization:

No Fiig: A073a0