NSN 5985-01-296-3004

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-296-3004 **Application Design:** Transmission line **Body Material:** Steel, corrosion resisting **Body Style:** Err-090 **Body Surface Treatment:** Passivated **Overall Length:** 1.200 inches **Operating Tempurature Range:** -55.0/+85.0 degrees celsius **Voltage Standing Wave Ratio:** 1.15 and 1.40 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Power Rating:** 2.0 watts average Rf Signal Attenuation In Decibels: 30.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+18.0 gigahertz and +18.0/+40.0 gigahertz **Attenuation Accuracy In Decibels:** -0.50/+0.50 **Connection Type Per Function:** Female input and male output **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 40.000 gigahertz **Fsc Application Data:** Antennas, waveguides, and related equipment Shelf Life: N/a **Unit Of Measure:**

--Demilitarization:

No

NSN 5985-01-296-3004

Fixed Attenuator - Page 2 of 2



Fiig:

A20000