NSN 5985-01-296-3004

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-296-3004

Application Design:

Transmission line

Body Material:

Steel, corrosion resisting

Body Style:

Err-090

Body Surface Treatment:

Passivated

Overall Length:

1.200 inches

Operating Tempurature Range:

-55.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.15 and 1.40

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Power Rating:

2.0 watts average

Rf Signal Attenuation In Decibels:

30.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+18.0 gigahertz and +18.0/+40.0 gigahertz

Attenuation Accuracy In Decibels:

-0.50/+0.50

Connection Type Per Function:

Female input and male output

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 40.000 gigahertz

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5985-01-296-3004

Fixed Attenuator - Page 2 of 2

Fiig: A20000

