## NSN 5985-01-296-3541

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-296-3541

Application Design:
Transmission line
Body Material:
Aluminum
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length:
2.930 inches
Overall Diameter:
1.550 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.20 and 1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
25.0 watts average and 5.0 kilowatts peak
25.0 watts average and 5.0 kilowatts peak  Rf Signal Attenuation In Decibels:
·
Rf Signal Attenuation In Decibels:
Rf Signal Attenuation In Decibels: 10.0
Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range:
Rf Signal Attenuation In Decibels: 10.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz
Rf Signal Attenuation In Decibels:  10.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz  Attenuation Accuracy Reference Frequency:
Rf Signal Attenuation In Decibels: 10.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz  Attenuation Accuracy Reference Frequency: 8.0 gigahertz
Rf Signal Attenuation In Decibels: 10.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz  Attenuation Accuracy Reference Frequency: 8.0 gigahertz  Attenuation Accuracy In Decibels:
Rf Signal Attenuation In Decibels:  10.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz  Attenuation Accuracy Reference Frequency: 8.0 gigahertz  Attenuation Accuracy In Decibels: -0.60/+0.60
Rf Signal Attenuation In Decibels: 10.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz  Attenuation Accuracy Reference Frequency: 8.0 gigahertz  Attenuation Accuracy In Decibels: -0.60/+0.60  Connection Type Per Function:
Rf Signal Attenuation In Decibels:  10.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz  Attenuation Accuracy Reference Frequency: 8.0 gigahertz  Attenuation Accuracy In Decibels: -0.60/+0.60  Connection Type Per Function: Female input and female output
Rf Signal Attenuation In Decibels:  10.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz  Attenuation Accuracy Reference Frequency: 8.0 gigahertz  Attenuation Accuracy In Decibels: -0.60/+0.60  Connection Type Per Function: Female input and female output  Unpackaged Unit Weight:
Rf Signal Attenuation In Decibels:  10.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz Attenuation Accuracy Reference Frequency: 8.0 gigahertz  Attenuation Accuracy In Decibels: -0.60/+0.60  Connection Type Per Function: Female input and female output Unpackaged Unit Weight: 6.000 ounces
Rf Signal Attenuation In Decibels:  10.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz  Attenuation Accuracy Reference Frequency: 8.0 gigahertz  Attenuation Accuracy In Decibels: -0.60/+0.60  Connection Type Per Function: Female input and female output  Unpackaged Unit Weight: 6.000 ounces  Mounting Method:
Rf Signal Attenuation In Decibels:  10.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz  Attenuation Accuracy Reference Frequency: 8.0 gigahertz  Attenuation Accuracy In Decibels: -0.60/+0.60  Connection Type Per Function: Female input and female output  Unpackaged Unit Weight: 6.000 ounces  Mounting Method: Connector
Rf Signal Attenuation In Decibels: 10.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz Attenuation Accuracy Reference Frequency: 8.0 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60  Connection Type Per Function: Female input and female output Unpackaged Unit Weight: 6.000 ounces Mounting Method: Connector Terminal Type And Quantity:

## NSN 5985-01-296-3541

Fixed Attenuator - Page 2 of 2



Fsc App	lication	Data:
---------	----------	-------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000