## NSN 5985-01-296-3542

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-296-3542

Application Design:
Transmission line
Body Material:
Steel, corrosion resisting
Body Style:
Rectangular, terminal/terminals on opposite surfaces
Body Surface Treatment:
Any acceptable
Overall Length:
3.160 inches
Overall Height:
0.990 inches
Overall Width:
0.990 inches
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
20.0 watts average and 0.5 kilowatts peak
Rf Signal Attenuation In Decibels:
22.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+12.4 gigahertz
Attenuation Accuracy Reference Frequency:
12.4 gigahertz
Attenuation Accuracy In Decibels:
-1.00/+1.00
Connection Type Per Function:
Female input and female output
Unpackaged Unit Weight:
8.000 ounces
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 12.400 gigahertz

## NSN 5985-01-296-3542

Fixed Attenuator - Page 2 of 2



Fsc Application Data	Fsc	Ap	plic	ation	Data
----------------------	-----	----	------	-------	------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000