# NSN 5985-01-298-3480

Fixed Attenuator - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5985-01-298-3480

## Application Design:

Transmission line

## **Body Material:**

Aluminum

## Body Style:

Err-090

### **Terminal Material:**

Steel, stainless

#### **Terminal Surface Treatment:**

Passivated

### Body Surface Treatment:

Paint, black

#### **Overall Length:**

1.900 inches

### **Overall Diameter:**

0.650 inches

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Voltage Standing Wave Ratio:

1.20 and 1.30 and 1.35

## Input Impedance Rating In Ohms:

50.0

### **Output Impedance Rating In Ohms:**

50.0

## **Coaxial Connector Series Designation:**

Sma

### **Power Rating:**

10.0 watts average and 1.0 kilowatts peak

### **Rf Signal Attenuation In Decibels:**

10.0

### Voltage Standing Wave Ratio Frequency Range:

+0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz

#### **Connection Type Per Function:**

Female input and female output

#### **Unpackaged Unit Weight:**

1.000 ounces

#### **Mounting Method:**

Connector

### **Terminal Type And Quantity:**

2 connector

#### **Frequency Range:**

Between 0.000 hertz and 18.000 gigahertz

# NSN 5985-01-298-3480

Fixed Attenuator - Page 2 of 2



## **Supplementary Features:**

Beryllium copper female contacts; rugged constr iaw mil-a-3933

# **Fsc Application Data:**

Antennas, waveguides, and related equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000