NSN 5985-01-298-5833

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-298-5833

Application Design:
Transmission line
Body Material:
Steel, corrosion resisting
Body Style:
1b round, terminal/terminals in opposite surface
Terminal Material:
Steel, corrosion resisting
Terminal Surface Treatment:
Passivated
Body Surface Treatment:
Passivated
Overall Length:
1.837 inches
Overall Diameter:
0.840 inches
Operating Tempurature Range:
+0.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.15
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
2.0 watts average and 500.0 watts peak
Rf Signal Attenuation In Decibels:
10.0
Voltage Standing Wave Ratio Frequency Range:
+420.0/+450.0 megahertz
Attenuation Accuracy In Decibels:
-0.15/+0.15
Connection Type Per Function:
Female input and male output
Unpackaged Unit Weight:
2.500 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector

2 connector

NSN 5985-01-298-5833

Fixed Attenuator - Page 2 of 2



Frequency	Range:
-----------	--------

Between 420.000 megahertz and 450.000 megahertz

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000