## NSN 5985-01-299-3701

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-299-3701

View Online at https://aerobasegroup.com/nsn/5985-01-299-3701
Cross Sectional Shape:
Internal, rectangular double ridged external, rectangular
Bend Angle In Deg:
90.0 single bend e-plane
Tubing Wall Construction Style:
Seamless single tubing segment
Flange Quantity:
2
Voltage Standing Wave Ratio:
1.20
Insertion Loss In Decibels:
0.15
Maximum Operating Pressure:
30.0 pounds per square inch gage
Waveguide Outside Width:
0.820 inches
Waveguide Outside Height:
0.420 inches
Waveguide Longer Offset Distance:
2.250 inches
Waveguide Offset Distance:
1.310 inches
Special Features:
Frequency range 8.7 to 20.2 ghz; pwr handling 6.0 kw peak
Flexibility:
Rigid single tubing segment
Material:
Aluminum alloy all tubing segment and flange
Surface Treatment:
Chromate all tubing segment and flange outside surfaces and primer all tubing segment and flange outside surfaces and enamel all tubing
segment and flange outside surfaces
Style Designator:
Bend type
Specification Data:
26916-037-003602 manufacturers source control
Fsc Application Data:
Antennas, waveguides and related equip.
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

## NSN 5985-01-299-3701

Waveguide Assembly - Page 2 of 2



Fiig:

A073a0