NSN 5985-01-304-6659

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-304-6659

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.705 inches second flange

Flange Inside Height:

0.394 inches second flange

Flange Outside Width:

1.860 inches second flange and 1.890 inches second flange

Flange Outside Height:

1.860 inches second flange and 1.890 inches second flange

Flange Inside Diameter:

0.985 inches first flange and 1.015 inches first flange

Flange Depth:

0.360 inches first flange and 0.390 inches first flange

Flange Connecting Hole Diameter:

0.144 inches second flange all connection facilities

Voltage Standing Wave Ratio:

```
1.10
```

Insertion Loss In Decibels:

0.25

Thready Qty Per Inch (tpi):

32 first flange all connection facilities

Maximum Operating Pressure:

5.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

Thread Size:

0.138 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.6195 inches and 0.6245 inches

Waveguide Inside Height:

Between 0.3085 inches and 0.3135 inches

Waveguide Outside Height:

Between 0.388 inches and 0.394 inches

NSN 5985-01-304-6659

Waveguide Assembly - Page 2 of 2



Waveguide Longer Offset Distance: Between 3.670 inches and 3.730 inches Flange Connecting Facility And Quantity: 4 unthreaded hole second flange all connection facilities Flange Style: Cover type second flange Waveguide Offset Distance: Between 2.170 inches and 2.220 inches **Special Features:** 12.4 to 18.0 ghz; do not paint flange faces Flexibility: Rigid single tubing segment Material: Aluminum alloy all tubing segment and flange **Surface Treatment:** Primer all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces Style Designator: Bend type **Thread Series Designator:** Unc first flange all connection facilities **Fsc Application Data:** Antennas, waveguides, and related equipment Shelf Life: N/a Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A073a0