## NSN 5985-01-304-6925

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-304-6925

Application Design:
Transmission line
Body Material:  Metal
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length: 1.250 inches
Overall Diameter:
0.400 inches
Voltage Standing Wave Ratio:
1.15 and 1.30 and 1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average and 200.0 watts peak
Rf Signal Attenuation In Decibels:
16.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz
Attenuation Accuracy Reference Frequency:
18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.60/+0.60
Unpackaged Unit Weight:
0.500 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:

N/a

## NSN 5985-01-304-6925

Fixed Attenuator - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000