

View Online at <https://aerobasegroup.com/nsn/5985-01-305-0941>

Application Design:

Transmission line

Body Style:

Irregular

Overall Height:

0.380 inches

Overall Width:

1.440 inches

Distance Between Mounting Facility Centers:

Between 1.183 inches and 1.193 inches

Operating Temperature Range:

-65.0/+100.0 degrees celsius

End Application:

Countermeasures set an/dlq-3 (v)

Voltage Standing Wave Ratio:

2.50

Coaxial Connector Series Designation:

Sma

Mounting Facility Screw Thread Series Designator:

Unc

Overall Attenuation Range In Decibels:

+2.5/+4.0

Attenuation Accuracy Reference Frequency:

4.0 gigahertz

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

2 threaded hole

Frequency Range:

Between 1.000 gigahertz and 18.000 gigahertz

Mounting Thread Quantity:

32 per inch

Adjustment Device Type And Quantity:

1 electronic, voltage controlled

Mounting Facility Pattern:

Two position in-line

Mounting Facility Screw Thread Diameter:

0.138 inches

Precious Material And Location:

Pin ext surface gold

Precious Material:

Gold

Terminal Type And Quantity:

1 connector, coaxial, female and 1 connector, coaxial, male and 2 pin

Fsc Application Data:

Antennas, waveguides, and related equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0