NSN 5985-01-305-4464

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-305-4464				
Application Design:				
Transmission line				
Body Style:				
Irregular				
Overall Length:				
2.260 inches				
Overall Height:				
0.380 inches				
Overall Width:				
1.880 inches				
Distance Between Mounting Facility Centers:				
1.750 inches				
Operating Tempurature Range:				
-65.0/+100.0 degrees celsius				
End Application:				
Countermeasures set an/dlq-3 (v)				
Voltage Standing Wave Ratio:				
2.50				
Coaxial Connector Series Designation:				
Sma				
Mounting Facility Screw Thread Series Designator:				
Unc				
Overall Attenuation Range In Decibels:				
+5.0/+8.0				
Attenuation Variation Method:				
Continuous				
Mounting Facility Type And Quantity:				
2 threaded hole				
Frequency Range:				
Between 1.000 gigahertz and 18.000 gigahertz				
Mounting Thread Quantity:				
32 per inch				
Adjustment Device Type And Quantity:				
1 electronic, voltage controlled				
Mounting Facility Pattern:				
Two position in-line				

0.138 inches

Supplementary Features:

Storage temp m60 to p125 degrees c

Mounting Facility Screw Thread Diameter:

Terminal Type And Quantity:

3 connector, coaxial, female and 4 solder stud and 3 turret

NSN 5985-01-305-4464

Variable Attenuator - Page 2 of 2



	Fsc	App	lication	Data:
--	-----	-----	----------	-------

Antennas, waveguides, and related equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0