NSN 5985-01-308-6680



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-308-6680 **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** Err-090 **Body Surface Treatment:** Passivated **Overall Length:** 2.280 inches **Overall Diameter:** 0.827 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.15 and 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Ν **Power Rating:** 5.0 watts average and 0.40 kilowatts peak **Rf Signal Attenuation In Decibels:** 1.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.0 gigahertz **Attenuation Accuracy In Decibels:** -0.40/+0.40 **Connection Type Per Function:** Female input and male output **Unpackaged Unit Weight:** 0.07 kilograms **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector

Frequency Range:

Between 0.000 hertz and 12.400 gigahertz

Precious Material And Location:

Contact surfaces gold

NSN 5985-01-308-6680

Fixed Attenuator - Page 2 of 2



_			
u	racialie	Material	•

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000