

View Online at <https://aerobasegroup.com/nsn/5985-01-309-4948>

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

3.640 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.600 inches

Overall Height:

0.800 inches

Overall Width:

1.870 inches

Voltage Standing Wave Ratio:

1.40

Coaxial Connector Series Designation:

Sma

Power Rating:

0.5 watts average

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

3.3

Overall Attenuation Range In Decibels:

+1.0/+32.0

Attenuation Accuracy Reference Frequency:

1.0 gigahertz

Attenuation Variation Method:

Stepped

Step Position Quantity:

6

Attenuation Per Step In Decibels:

1.0 and 2.0 and 4.0 and 8.0 and 16.0 and 32.0

Mounting Facility Type And Quantity:

4 threaded hole

Frequency Range:

Between 0.000 hertz and 1.500 gigahertz

Segment Attenuation Range In Decibels:

+1.00/+2.00 and +2.00/+4.00 and +4.00/+8.00 and +8.00/+16.00 and +16.00/+32.00

Mounting Thread Quantity:

56 per inch

Adjustment Device Type And Quantity:

1 electronic, programmable

Mounting Facility Pattern:

Four position rectangular

Mounting Facility Screw Thread Diameter:

0.086 inches

Impedance Rating In Ohms:

50.0 input-output

Mounting Thread Tolerance Class:

2b external

Terminal Type And Quantity:

2 connector, coaxial, female and 1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0