

View Online at <https://aerobasegroup.com/nsn/5985-01-309-4948>

**Application Design:**

Transmission line

**Body Style:**

Coaxial type

**Overall Length:**

3.640 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.375 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.600 inches

**Overall Height:**

0.800 inches

**Overall Width:**

1.870 inches

**Voltage Standing Wave Ratio:**

1.40

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

0.5 watts average

**Mounting Facility Screw Thread Series Designator:**

Unc

**Insertion Loss At Minimum Attenuation In Maximum Decibels:**

3.3

**Overall Attenuation Range In Decibels:**

+1.0/+32.0

**Attenuation Accuracy Reference Frequency:**

1.0 gigahertz

**Attenuation Variation Method:**

Stepped

**Step Position Quantity:**

6

**Attenuation Per Step In Decibels:**

1.0 and 2.0 and 4.0 and 8.0 and 16.0 and 32.0

**Mounting Facility Type And Quantity:**

4 threaded hole

**Frequency Range:**

Between 0.000 hertz and 1.500 gigahertz

**Segment Attenuation Range In Decibels:**

+1.00/+2.00 and +2.00/+4.00 and +4.00/+8.00 and +8.00/+16.00 and +16.00/+32.00

**Mounting Thread Quantity:**

56 per inch

**Adjustment Device Type And Quantity:**

1 electronic, programmable

**Mounting Facility Pattern:**

Four position rectangular

**Mounting Facility Screw Thread Diameter:**

0.086 inches

**Impedance Rating In Ohms:**

50.0 input-output

**Mounting Thread Tolerance Class:**

2b external

**Terminal Type And Quantity:**

2 connector, coaxial, female and 1 connector, receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A223a0