NSN 5985-01-310-5436

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-310-5436 **Application Design:** Transmission line **Body Style:** Cylindrical w/rear terminals **Overall Length:** 3.680 inches **Body Length:** 2.520 inches **Overall Diameter:** 1.630 inches **Voltage Standing Wave Ratio:** 1.25 **Coaxial Connector Series Designation:** Wpm **Power Rating:** 2.0 watts average and 200.0 watts peak **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 0.4 **Overall Attenuation Range In Decibels:** +0.0/+60.0 **Attenuation Variation Method:** Stepped **Step Position Quantity: Attenuation Per Step In Decibels:** 10.0 **Mounting Facility Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 4.000 gigahertz **Adjustment Device Type And Quantity:** Impedance Rating In Ohms: 50.0 input-output **Terminal Type And Quantity:** 2 connector, coaxial, female Shelf Life: N/a **Unit Of Measure:**

Demilitarization: Yes - demil/mli

NSN 5985-01-310-5436

Variable Attenuator - Page 2 of 2



Fiig:

A223a0