## NSN 5985-01-310-7718

Waveguide Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-310-7718

End Application:
Directional antenna
Tubing Wall Construction Style:
Seamless all tubing segment
Flange Quantity:
2
Voltage Standing Wave Ratio:
1.40
Insertion Loss In Decibels:
0.10
Maximum Operating Pressure:
6.0 pounds per square inch gage
Waveguide Center To Center Distance:
8.500 inches
Flexibility:
Flexible all tubing segment
Material:
Copper alloy all tubing segment
Copper alloy all tubing segment  Surface Treatment:
Surface Treatment:
Surface Treatment: Paint all tubing segment all surfaces
Surface Treatment: Paint all tubing segment all surfaces Style Designator:
Surface Treatment: Paint all tubing segment all surfaces Style Designator: Double bend type
Surface Treatment: Paint all tubing segment all surfaces Style Designator: Double bend type Shelf Life:
Surface Treatment: Paint all tubing segment all surfaces Style Designator: Double bend type Shelf Life: N/a
Surface Treatment: Paint all tubing segment all surfaces Style Designator: Double bend type Shelf Life: N/a Unit Of Measure:
Surface Treatment: Paint all tubing segment all surfaces Style Designator: Double bend type Shelf Life: N/a Unit Of Measure:
Surface Treatment: Paint all tubing segment all surfaces Style Designator: Double bend type Shelf Life: N/a Unit Of Measure: Demilitarization:
Surface Treatment: Paint all tubing segment all surfaces Style Designator: Double bend type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli
Surface Treatment: Paint all tubing segment all surfaces Style Designator: Double bend type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:
Surface Treatment: Paint all tubing segment all surfaces Style Designator: Double bend type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: